

## SYN-TEC MF 5W30

### DESCRIPTION :

SYN-TEC MF 5W30 is a synthetic, fuel economy "MID SAPS" motor oil especially designed for FORD.

### ADVANTAGES :

Provides Fuel Economy (>3%).

Reduces exhaust of harmful emissions.

Guarantees a quick cold start, even at -30°C.

Excellent fluidity even with very high operating temperature and speed.

Extremely suitable for cars equipped with catalists and particulate filters.

### SPECIFICATIONS :

SYN-TEC MF 5W30 meets the following specifications:

ACEA A5/B5-08  
FORD WSS-M2C-913-C

### APPLICATIONS :

SYN-TEC MF 5W30 is especially designed for the newest generation FORD engines, gasoline engines and diesel engines with diesel particulate filters (DPF), This oil can not be used for engines equipped with pump-injectors. (Ford Galaxy I & II and Ford KA (gasoline & diesel from 2009))

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m <sup>3</sup>	852
Viscosity at 40°C	D 445	cSt	52
Viscosity at 100°C	D 445	cSt	9.6
Viscosity at -30°C	D 5293	cP	4200
Viscosity index	D 2270		172
Flash point COC	D 92	°C	226
Pour point	D 6892	°C	-37
TBN	D 2896	g KOH/kg	8,5
Sulphated ash	D 874	mass %	0,8

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

