

## PRO FLEET 15W40

UNIVERSAL MOTOR OIL FOR GASOLINE AND DIESEL ENGINES.

### DESCRIPTION :

PRO FLEET 15W40 is a universal motor oil, suitable for all 4-stroke gasoline and diesel engines.

### ADVANTAGES :

Very high resistance against oxidation and piston deposits.

High detergent and dispersant properties.

High neutralizing power.

Strong resistance.

High lubrication power.

Very large application field.

Low loss by evaporation.

### SPECIFICATIONS :

API	SJ/CG-4, CF	MB	228.1, 229.1
ACEA	A3-98	MAN	271
	B3-98	ALLISON	C4
	B4-98	CAT	TO-2
	E2-96 - Issue 2	VOLVO	VDS

### APPLICATIONS :

PRO FLEET 15W40 are universal motor oils, for use in high speed four stroke-cycle diesel engines used on both heavy-duty on-highway (less than 0,05% wt. sulphur fuel) and off-highway (less than 0,5% wt. sulphur fuel) applications. These oils are especially effective in engines designed to meet 1994 emission standards.

These oils can be used in all gasoline engines according to the severe service prescriptions.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			15W40
Density at 15°C	D 4052	kg / m <sup>3</sup>	882
Viscosity at -20°C	D 5293	cP	6600
Viscosity at 40°C	D 445	cSt	107
Viscosity at 100°C	D 445	cSt	14,0
Viscosity index	D 2270		136
Pour point	D 6892	°C	-30
TBN	D 2896	g KOH/kg	6,9
Flash point COC	D 92	°C	228
Sulphated ash	D 874	mass %	1,05
Loss by evaporation	NOACK	mass %	13,0

