

RACING PLUS 5W50

FULLY SYNTHETIC RACING MOTOR OIL.

DESCRIPTION:

RACING PLUS 5W50 is a fully synthetic engine oil of the latest generation, for the lubrication of all high performance engines.

ADVANTAGES:

- Excellent fluidity at low temperature.
- Very low resistance at start.
- Exceptional viscosity index.
- Very high thermal stability.

SPECIFICATIONS:

API	SJ, SL/CF
ACEA	A3/B3
VW	501.01 / 505.00
BMW	
PORSCHE	

APPLICATIONS:

- 4-stroke gasoline engines, multi-valves, turbo.
- 4-stroke passenger car diesel engines, with or without turbo.

TYPICAL CHARACTERISTICS:

Test	Method	Unit	Average result
SAE-class			5W50
Density at 15°C	D 4052	kg / m ³	855
Viscosity at 40°C	D 445	cSt	118
Viscosity at 100°C	D 445	cSt	18
Viscosity at -30°C	D 5293	cP	5850
Viscosity index	D 2270		172
Pour point	D 6892	°C	-40
TBN	D 2896	g KOH/ kg	9,5
Flash point	D 92	°C	235
Sulphated ash	D 874	mass %	1,0
Loss by evaporation	NOACK	mass %	8

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.





Esserstraat 10 - 8550 Zwevegem - Tel.: +32 (0)56 72 62 29 - Fax: +32 (0)56 72 67 37

www.ardeca-lubricants.be