

## MATIC + III ATF

### FLUID FOR AUTOMATIC TRANSMISSIONS.

#### DESCRIPTION :

MATIC + III ATF is an oil with a high viscosity index for automatic transmissions.

#### ADVANTAGES :

High chemical stability.  
Small viscosity change in function of temperature.  
Increased anti-wear properties.  
Excellent oxidation stability.

#### SPECIFICATIONS :

GM	DEXRON III G (GM 6417M)	MAN	339 F
FORD	MERCON	ZF	TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C
	WSA-M2C-195A (Service Fill)	HAGGLUNDS-	HF-0
ALLISON	C4	DENISON	
CAT	TO-2	VOITH	55.6335 (G607)
MB	236.1, 236.5, 236.6, 236.7		

#### APPLICATIONS :

MATIC + III ATF can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the constructors prescribe a product, which meets the GENERAL MOTORS ATF TYPE DERON III or DEXRON II E and FORD MERCON-requirements.

#### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density at 15°C	D 4052	kg / m <sup>3</sup>	862
Viscosity at 40°C	D 445	cSt	34,3
Viscosity at 100°C	D 445	cSt	7,7
Viscosity index	D 2270		205
Pour point	D 6892	°C	-45
Flash point COC	D 92	°C	196
Brookfield viscosity	D 2893	mPa.s	18400
Colour			red

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

