

MATIC +

FLUID FOR AUTOMATIC TRANSMISSIONS.

MATIC + is an oil with a high viscosity index for automatic transmissions.

MATIC + meets the following specifications:

- GM 6137-M DEXRON ® II-D
- FORD M2C 166H, Mercon
- ALLISON C4
- CAT TO-2
- MB 236.1, 236.5, 236.6, 236.7
- MAN 339 D
- ZF TE-ML 02F, 03D, 04D, 09, 11A, 14A, 17C
- VOITH 55.6335 (G 607)

AVANTAGES :

- High chemical stability.
- Small viscosity change in function of temperature.
- Increased anti-wear properties.
- Excellent oxidation stability.

APPLICATIONS :

MATIC + can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the constructors prescribe a product, which meets the GENERAL MOTORS ATF TYPE DEXRON II E and FORD MERCON-requirements.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Colour			Red
Density at 15°C	D4052	kg/m ³	865
Viscosity at 40°C	D445	cSt	35
Viscosity at 100°C	D445	cSt	7,4
Viscosity index	D2270		180
Pour point	D6892	°C	-39
TBN	D2896	gKOH/kg	2,2
Flash point COC	D92	°C	205

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

