# POWER 2T ZTT

POWER 2T ZTT is a semi-synthetic prediluted oil, intended for the lubrication of 2-stroke gasoline engines with high specific power.This oil combines a high lubricity with a high thermal stability. Easily miscible with gasoline and efficient protection against deposits.

POWER 2T ZTT meets the following specifications:

- API TC
- JASO FD
- ISO-L EGB
- GLOBAL GD
- HUSQVARNA 272 2-Stroke DFI

***APPLICATIONS :***

This oil is especially manufactured in order to satisfy the requirements of modern air cooled 2-stroke engines with a high specific power. Limited smoke formation.

***TYPICAL CHARACTERISTICS :***

| *Test* | *Method* | *Unit* | *Average result* |
|---|---|---|---|
| Colour | | | Green |
| Density at 15°C | D4052 | kg/m$^3$ | 882 |
| Viscosity at 40°C | D445 | cSt | 78,4 |
| Viscosity at 100°C | D445 | cSt | 10,2 |
| Viscosity index | D2270 | | 112 |
| Pour point | D6892 | °C | -15 |
| TBN | D2896 | gKOH/kg | 1,1 |
| Flash point COC | D92 | °C | 100 |

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

***VROMAN NV - Oudenaardestraat 49 - 8570 Vichte - Tel.: +32 (0)56 72 62 29 - Fax: +32 (0)56 72 67 37***

**www.ardeca-lubricants.be**