

SYNTH XL 5W40

SYNTH XL 5W40 is a lubricant on synthetic base, especially designed to answer the highest VW-specifications (VW 505.01) for diesel engines. By using the latest technologies, this engine oil provides an excellent performance on the latest Tdi-engines with pump injector units and a high protection of the exhaust catalyst.

SYNTH XL 5W40 meets the following specifications:

- API SN/CF
- BMW LONGLIFE -04
- ACEA A3/B4-04 / C3-08
- PORSCHE A40
- MB 229.31, MB 229.51
- FORD WSS-M2C 917-A
- VW 505.01, 502.00 / 505.00 (2005)

APPLICATIONS :

This oil was specially formulated for the lubrication of all TDI engines with pump injectors. It is also suitable for most Euro - 4 engines of passenger cars.

TYPICAL CHARACTERISTICS :

<i>Test</i>	<i>Method</i>	<i>Unit</i>	<i>Average result</i>
SAE-class			5W40
Density at 15°C	D4052	kg/m ³	850
Viscosity at 40°C	D445	cSt	82,80
Viscosity at 100°C	D445	cSt	14,00
Viscosity at -30°C	D5293	cP	5500
Viscosity index	D2270		175
Flash point COC	D92	°C	232
Pour point	D6892	°C	-42
TBN	D2896	gKOH/kg	7,7
Sulfated ash	D874	mass %	0,77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.