

## **MATIC + III H**

### **FLUID FOR AUTOMATIC TRANSMISSIONS.**

MATIC + III H is a very high grade transmission fluid formulated with selected additives to obtain the following properties:

- High and stable viscosity index.
- Small viscosity change in function of temperature.
- A very low pour point.
- Excellent oxidation stability.
- A positive activity against wear, corrosion and foam.
- Specific friction properties.
- A perfect compatibility with seals and non-ferro metals.

MATIC + III H meets the following specifications:

- GM DEXRON III H
- FORD MERCON
- ALLISON C4 / TES 389
- CAT TO-2
- MB 236.1, 236.5
- MAN 339 Z1/V1
- ZF TE-ML 09B, 11B, 14A
- DENISON
- VOITH 55.6335 (G607)
- VOLVO CE 97241

### **APPLICATIONS :**

MATIC + III H can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the constructors prescribe a product, which meets the GENERAL MOTORS ATF TYPE DERON III H and FORD MERCON-requirements.

### **TYPICAL CHARACTERISTICS :**

Test	Method	Unit	Average result
Density at 15°C	D4052	kg/m <sup>3</sup>	858
Viscosity at 40°C	D445	cSt	36,2
Viscosity at 100°C	D445	cSt	7,45
Viscosity index	D2270		178
Pour point	D6892	°C	-51
Flash point COC	D92	°C	216
Total Base Number		mgKOH/g	2,4
Colour			red

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

