

COOLANT PLUS

G11 engine coolant

COOLANT PLUS is an ethylene glycol based engine coolant formulated for use in all engines including those constructed from aluminium alloys. It employs established inhibitor technology and is nitrite, amine and phosphate (NAP) free and includes borate and silicate. BTC classification Type 2E.

COOLANT PLUS uses sophisticated silicate stabilisation technology to eliminate the potential for formation of silicate gel often observed with inferior products whilst other additives ensure good compatibility with hard water and prevent the formation of scale that can result from use of hard water.

It has the following properties:

Specific Gravity 20/4°C	1.074
Freeze Protection * °C	-35

PERFORMANCE LEVEL :

COOLANT PLUS exceeds the requirements of most European and International Standards including: ASTM D3306, ASTM D 4985, SAE J 1034, BS 6580 (1992), AFNOR NF R15-601

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Appearance	Visual	Green - Blue	Not Specified
Specific Gravity 15/15°C	ASTM D 4052	1.045	1.110 - 1.145
Equilibrium Reflux Boiling Point °C	ASTM D 1120	170	163 min
Freezing Point °C	ASTM D 1177	-35	-37 max
pH	ASTM D 1287	7.8	7.5 - 11.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

