

SYNTH-V 0W30

FULLY SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils that was especially developed to meet the requirements of Volvo passenger cars. It is characterized by increased lubricating properties and a better fuel economy. In this way it procures a reduced fuel consumption and a longer lifetime of the engine.

SYNTH-V 0W30 meets the following specifications:

- ACEA A5/B5
- API SL/CF

APPLICATIONS :

This oil is recommended for the gasoline and diesel models of Volvo Cars of the latest generations, equipped with 5-cylinder engines.

FEATURES :

Cold start : very good fluidity at low temperature.

Total engine protection : performance in keeping the engine clean.

Fuel economy : superior fuel economy and CO2 reduction.

TYPICAL CHARACTERISTICS :

<i>Test</i>	<i>Method</i>	<i>Unit</i>	<i>Average result</i>
Density @ 15°C	ASTM D4052	g/ml	0,850
Viscosity @40°C	ASTM D445	mm ² /s	55,2
Viscosity @100°C	ASTM D445	mm ² /s	10,3
Viscosity index	ASTM D2270		178
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10,0
Pour Point	ASTM D6892	°C	-51
Sulfated Ash	ASTM D874	Mass %	1,09
Flash Point COC	ASTM D92	°C	220
CCS Viscosity @-35°C	ASTM D5293	mPa.s	6000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.